

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

1 Identification

Product identifier

- Trade name: **Akepox Colouring pastes**
- Article number: 11220, 11221, 11222, 11223, 11224, 11225, 11226, 11227, 11228
- Relevant identified uses of the substance or mixture and uses advised against: No further relevant information available.
- Application of the substance / the mixture: Stainer

Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de
- Information department: Laboratory
- Emergency telephone number: Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

2 Hazard(s) identification

Classification of the substance or mixture



GHS07

- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2A H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Irritant

Irritating to eyes and skin. May cause sensitization by skin contact.



Dangerous for the environment

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

Label elements

Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

Code letter and hazard designation of product:



Xi Irritant
N Dangerous for the environment

Hazard-determining components of labeling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

Trade name: Akepox Colouring pastes

(Contd. of page 1)

- reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)
1.6-hexanediol diglycidyl ether
- Risk phrases:** Irritating to eyes and skin.
May cause sensitization by skin contact.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
- Safety phrases:** Keep out of the reach of children.
Do not breathe vapour.
Avoid contact with skin and eyes.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
Wear suitable protective clothing, gloves and eye/face protection.
In case of insufficient ventilation, wear suitable respiratory equipment.
If swallowed, seek medical advice immediately and show this container or label.
Use only in well-ventilated areas.
- Special labeling of certain preparations:** Contains epoxy constituents. See information supplied by the manufacturer.
- Classification system:**
- NFPA ratings (scale 0 - 4)**

0	0	1
Health = 1	Fire = 0	Reactivity = 0
- HMIS-ratings (scale 0 - 4)**

HEALTH 1	Health = 1
FIRE 0	Fire = 0
REACTIVITY 0	Reactivity = 0
- Other hazards**
- Results of PBT and vPvB assessment**
- PBT:** Not applicable.
- vPvB:** Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures**
- Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) ☒ Xi R36/38-43; ☒ N R51/53 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 9003-36-5	reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700) ☒ Xi R38-43; ☒ N R51/53 ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	<12.5%
CAS: 16096-31-4 EINECS: 240-260-4	1.6-hexanediol diglycidyl ether ☒ Xi R36/38-43 R52/53 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	<12.5%

- Additional information:** For the wording of the listed risk phrases refer to section 16.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

Trade name: Akepox Colouring pastes

(Contd. of page 2)

4 First-aid measures**Description of first aid measures**

- General information: Take affected persons out into the fresh air.
- After inhalation: Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Rinse out mouth and then drink plenty of water.
- Information for doctor: Bisphenol-A based resins: Inhalation, swallowing or dermal incorporation may cause health damage. Irritates respiratory tract, digestion system, eyes and skin: e.g., cough, dyspnea, lacrimation, burning. May cause health interferences such as dermal changes, renal, hepatic damage, and blood count changes. May provoke skin allergies. Sensitized users can react towards very low concentrations of Bisphenol-A-Epichlorhydrine and should avoid any further contact with this chemical.
The sensitizing effect of epoxide based resins is mainly caused by the concentration of epoxy resin polymers with a specific molecular weight ≤ 300 . The observed allergic dermal and respiratory appearances should be treated symptomatically in dependence of the severity. An epoxy resin based allergic disease belongs to a cell mediated (interaction of lymphocytes) type IV allergy.
- Most important symptoms and effects, both acute and delayed Allergic reactions
- Danger Danger of impaired breathing.
Skin contact with polyester and epoxy resin solutions as ingredient of the product should be avoided due to risks of skin irritations or allergic skin appearances. If occasional hand contact can not be avoided, protection gloves, proper protection ointments and protective agents generating a protective layer on the skin were applied.
- Indication of any immediate medical attention and special treatment needed If swallowed, gastric irrigation with added, activated carbon.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO)
In certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen chloride (HCl)
- Advice for firefighters
- Protective equipment: Wear fully protective suit.
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

Trade name: Akepox Colouring pastes

(Contd. of page 3)

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to penetrate the ground/soil.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Dispose of the collected material according to regulations.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Keep receptacles tightly sealed.
Store in cool, dry place in tightly closed receptacles.
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from reducing agents.
Store away from foodstuffs.
- **Further information about storage conditions:** Store receptacle in a well ventilated area.
Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
The lists that were valid during the creation were used as basis.
- **Additional information:**
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Do not eat, drink, smoke or sniff while working.

(Contd. on page 5)

USA

Safety Data Sheet


acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

Trade name: Akepox Colouring pastes

(Contd. of page 4)

- Use skin protection cream for skin protection.
Clean skin thoroughly immediately after handling the product.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Short term filter device:
Filter A/P2
- Protection of hands: Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.
Akemi skin protection agent recommendation for preventive skin shelter without use of protective gloves:
ARRETIL (<http://www.stoko.com>)
Akemi skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
STOKO EMULSION (<http://www.stoko.com>)
Akemi skin protection recommendation for skin cleaning after product handling:
SLIG SPEZIAL (<http://www.stoko.com>)
Akemi skin protection agent recommendation for skin aftercare:
STOKO VITAN (<http://www.stoko.com>)
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).
-  Protective gloves
- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves Butyl rubber, BR
Chloroprene rubber, CR
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material Value for the permeation: Level \leq 6, 480 min
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014


Trade name: Akepox Colouring pastes

(Contd. of page 5)

- For the permanent contact gloves made of the following materials are suitable:
 - Butyl rubber, BR
 - Butoject (KCL, Art No. 897, 898)
 - Nitrile rubber, NBR
 - Dermatril (Art No. 740, 741, 742)
 - Camatril (KCL, Art No. 730, 731, 732, 733)
 - Chloroprene rubber, CR
 - Camapren (KCL, Art No. 720, 722, 726)

- As protection from splashes gloves made of the following materials are suitable:
 - Nitrile rubber, NBR
 - Dermatril (KCL, Art No. 740, 741, 742)
 - Camatril (KCL, 730, 731, 732, 733)
 - Natural rubber, NR
 - Combi-Latex (KCL, Art No. 395)

- Not suitable are gloves made of the following materials:
 - Leather gloves
 - Strong gloves

- Eye protection:
 -  Tightly sealed goggles

- Body protection:
 - Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Pasty
 Color: Different according to coloring
 Odor: Characteristic

· pH-value: Not applicable

· Change in condition

Melting point/Melting range: Undetermined.
 Boiling point/Boiling range: > 200 °C (> 392 °F)

· Flash point: Not applicable.

· Ignition temperature: > 300 °C °C (> 572 °C °F)

· Decomposition temperature: > 200 °C °C (> 392 °C °F)

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Vapor pressure at 20 °C (68 °F): 2 hPa (2 mm Hg)

· Density at 20 °C (68 °F): 1.57 g/cm³ (13.102 lbs/gal) ([1,43-1,78 g/cm³])

· Specific gravity at 20 °C (68 °F): 1.57 g/cm³ (13.102 lbs/gal) (1.43-1.78)

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Viscosity:

Dynamic at 20 °C (68 °F): 23000 mPas

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

Trade name: Akepox Colouring pastes

(Contd. of page 6)

· Solvent content:	
Organic solvents:	0.0 %
· Solids content:	
49.8 %	
· Other information	
No further relevant information available.	

10 Stability and reactivity

- **Reactivity**
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** May produce violent reactions with bases and numerous organic substances including alcohols and amines.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Irritant gases/vapors

11 Toxicological information

- **Information on toxicological effects**
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	LD50	20000 mg/kg (mouse)
		19800 mg/kg (rabbit)
		11400 mg/kg (rat)
Dermal	NOEL	540 mg/kg (rat) (OECD 416)
	LD50	1270 mg/kg (mouse) > 2000 mg/kg (rabbit) > 1200 mg/kg (rat)

9003-36-5 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit) >2000 mg/kg (rat)

- **Primary irritant effect:**
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- **Additional toxicological information:** The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

Trade name: Akepox Colouring pastes

(Contd. of page 7)

· NTP (National Toxicology Program)

None of the ingredients is listed.

* 12 Ecological information

· Toxicity

· Aquatic toxicity:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

EC50/24h	1.1-3.6 mg/l (daphnia magna)
EC50/48h	2.8 mg/l (daphnia magna)
EC50/72h	9.4 mg/l (selenastrum capricornutum)
EC50/96h	220 mg/l (green alge)
	3.6 mg/l (Leuciscus idus)
IC50	>100 mg/l (bacteria)
LC50/96h	1.3 mg/l (piscis)
	1.5 mg/l (Oncorhynchus mykiss) (OECD 203)
	1.5-7.7 mg/l (rainbow trout)
NOEC	0.3 mg/kg (daphnia magna) (OECD 211)

9003-36-5 reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

EC50/48h	1.6 mg/l (daphnia magna) (OECD 202: Part I)
EC50/72h	1.8 mg/l (green alge) (OECD 201)
IC50	>100 mg/l (bacteria)
LC50/96h	0.55 mg/l (piscis) (OECD 203)
NOEC	0.3 mg/kg (daphnia magna) (OECD 211)

 · **Persistence and degradability** No further relevant information available.

· Behavior in environmental systems:

 · Bioaccumulative potential No further relevant information available.

 · Mobility in soil No further relevant information available.

· Ecotoxicological effects:

 · Remark: Toxic for fish

· Additional ecological information:

 · General notes: Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (Self-assessment): hazardous for water

· Results of PBT and vPvB assessment

 · PBT: Not applicable.

 · vPvB: Not applicable.

 · Other adverse effects No further relevant information available.

* 13 Disposal considerations

· Waste treatment methods

 · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

Trade name: Akepox Colouring pastes

(Contd. of page 8)

· Uncleaned packagings:

· Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA

UN3082

· UN proper shipping name

· DOT

Environmentally hazardous substances, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))

· ADR

3082 Environmentally hazardous substances, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))

· IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT

· IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))

· Transport hazard class(es)

· DOT, IMDG, IATA



· Class

9 Miscellaneous dangerous substances and articles.

· Label

9

· ADR



· Class

9 (M6) Miscellaneous dangerous substances and articles

· Label

9

· Packing group

· DOT, ADR, IMDG, IATA

III

· Environmental hazards:

· Marine pollutant:

Product contains environmentally hazardous substances:

Yes

Symbol (fish and tree)

· Special marking (ADR):

Symbol (fish and tree)

· Special marking (IATA):

Symbol (fish and tree)

· Special precautions for user

· Danger code (Kemler):

Warning: Miscellaneous dangerous substances and articles

90

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

Trade name: Akepox Colouring pastes

(Contd. of page 9)

- | | |
|--|--|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Remarks: | Special marking with the symbol (fish and tree). |
| · UN "Model Regulation": | UN3082, Environmentally hazardous substances, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III |

15 Regulatory information**· Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

Trade name: Akepox Colouring pastes

(Contd. of page 10)

Hazard symbols:

Xi Irritant
N Dangerous for the environment

Hazard-determining components of labeling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
reaction product: bisphenol F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)
1.6-hexanediol diglycidyl ether

Risk phrases:

Irritating to eyes and skin.
May cause sensitization by skin contact.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Safety phrases:

Keep out of the reach of children.
Do not breathe vapour.
Avoid contact with skin and eyes.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
Wear suitable protective clothing, gloves and eye/face protection.
In case of insufficient ventilation, wear suitable respiratory equipment.
If swallowed, seek medical advice immediately and show this container or label.
Use only in well-ventilated areas.

Special labeling of certain preparations:

Contains epoxy constituents. See information supplied by the manufacturer.

National regulations:Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning young persons must be observed.

Water hazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

VOC USA

0.0 g/l

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing MSDS:

Laboratory

Contact:

Dieter Zimmermann
Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de

Date of preparation / last revision

01/22/2014 / -

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organization
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

(Contd. on page 12)

USA

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/22/2014

Reviewed on 01/22/2014

Trade name: Akepox Colouring pastes

(Contd. of page 11)

CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

USA